



High density rack tray with fully featured USB, PS2, SUN and Video control for critical environments

ADDERView® RDX 1000 IP

High density fully featured control for local, remote and global users

PRODUCT IN BRIEF

The ADDERView RDX 1000 IP is the complete server room solution with local and remote management. The I/O key-board tray is available in most keyboard language layouts and features either a 17 inch or 19 inch premium quality Samsung® SXGA 1280 x 1024 TFT LCD panel with touch-pad control and advanced OSD for device selection. Control up to 16 computers directly from the tray or remotely via a secure IP connection. Expand to support up to 256 computers using CATx 1000 switches.

Using Adder's CAM modules, you can connect the switch via CATx cable to any type of server including PC, Mac and Sun. Country code reporting, DDC and continuous keyboard and mouse emulation further ensure faultless operation across your unique installation.



FEATURES

One local and one IP user

Enables a global user to connect via IP and share access to any of the 16 connected computers.

Global user (IP)

Use Java web browsers or RealVNC® client software that, unlike HTTPS web browsers, is designed specifically for secure, high performance KVM over IP applications. Up to 1600 x 1200 resolutions with scalable windows.

True multi-platform capability and connectivity

The RDX 1000 supports any computer platforms with PS/2, USB or Sun keyboard and mouse interfaces.

LDAP integration plus ADDER.Net management software

Automating the task of managing your network hardware and authenticating users against your existing LDAP infrastructure.

RS232 port

Integrated RS232 gives you the ability to control other external devices such as power management devices.

Configuration and extension

The RDX allows you to configure 16 separate users internally with unique access privileges all of which are stored within the switch. Cascading a single CATx 1000 from the unit will enable control of 31 computers from one remote. Expand further simply by using just CATx cable

to more units. Cascade connections are automatically detected to support up to 256 computers.

Encryption and authentication

The enterprise grade integrated KVM over IP switch employs AES128 bit encryption and RSA2048 authentication ensuring your control system remains secure at all times.

Intelligent video thresholding

Adder's innovative active de-artifacting technology automatically calculates the ideal threshold for any computer or KVM switch so that video displays are refreshed with optimum immediacy - while "screen junk" is kept to an absolute minimum.

Flexible IP screen scaling

Adder solutions provide point-and-click screen scaling, so that users can quickly accommodate target devices running any size display with any aspect ratio. Adder solutions also allow users to easily override scaling if and when they require unscaled pixel-to-pixel mapping.

ADDERView® RDX 1000 IP

High density fully featured control for local, remote and global users

ABOUT ADDER

Adder is a leading developer and thought leader in connectivity solutions. Adder's advanced range of KVM switches, extenders and IP solutions enable the control of local, remote and global IT systems across the enterprise. The company distributes its products in more than 60 countries through a network of distributors, resellers and OEMs. Adder has offices in the United States, United Kingdom, Germany, the Netherlands, Sweden, China and Singapore.

To find out more, visit:
<https://www.adder.com>

TECHNICAL SPECIFICATIONS

Video Modes

Support for standard PC, Sun and Mac video modes.

Operating Systems and Software Compatibility

Software: All commonly known software and operating systems including Windows®, Linux®, macOS®, and Sun OS.

Extendable platform

Cascade with CATx 1000 units to extend the system to 256 computers and a global IP user.

Connections

CATx computer connections: all RJ45 style. 10/100 auto-sensing Ethernet network port: RJ45. Power connection: Locking 3 pin connector (12V DC, 5A). RS232 triggered power switching and syncing: DB9 plug.

Physical design

Compact 1U high metal case construction for rack mounting
Width: 589mm/17.4", Height: 44mm/1.76", Depth: 650mm/25.6".
Weight: RD1716IPxx 15kg/33lbs, RD1916IPxx 17kg/37lbs.

Power supply

Mains adapter with IEC style power lead (included).
Input: 100-240VAC 0.5A 50-60Hz.
Output: 12VDC 5A

Operating temperature

0 to 35°C

Approvals

CE, FCC, UKCA

ORDERING INFORMATION

RD1716IP-XX: RDX 1000 IP with 17 inch monitor
RD1916IP-XX: RDX 1000 IP with 19 inch monitor

XX	= Keyboard type + Mains Lead Country Code:
UK	= English Keyboard + UK IEC
US	= US English keyboard + USA IEC
IT	= Italian keyboard + Euro IEC
AUS	= English keyboard + AUS IEC
ES	= Spanish keyboard + Euro IEC
DE	= German keyboard + Euro IEC
NL	= Dutch keyboard + Euro IEC
NO	= Norwegian keyboard + Euro IEC
CH	= Swiss keyboard + Euro IEC
RU	= Russia keyboard + Euro IEC
CN	= Chinese keyboard + USA IEC
JP	= Japanese keyboard + USA IEC
FR	= French keyboard + Euro IEC

ADDITIONAL ACCESSORIES

CAM: Computer Access Modules
DisplayPort® connector, USB plus audio: CATXDP-USBA
Mini DisplayPort® connector, USB plus audio: CATX-MDP-USBA
VGA and PS/2: CATX-PS2
VGA and USB: CATX-USB
VGA, Sun plus audio: CATX-SUNA



Example CAM: CATX-USBA

RELATED PRODUCTS

Adder offer a vast range of products to suit your needs. Other products you may be interested in include:

ADDERView CATxIP
5000
AVX5016IP



ADDERView CATx IP
AVX4016; AVX4016IP;
AVX4024; AVX4024IP



ADDERLink® ipeps+
IPEPS-PLUS



ADDERLink® ipeps
AL-IPEPS; AL-IPEPS-DA



Adder and the Adder logo are trademarks of Adder Technology Ltd, Cambridge, UK. All other trademarks are the property of their respective owner and may be registered in the United States Patent and Trademark Office and in other countries. Copyright 2021 | Adder Technology Ltd. | ADDER_DS049_EN_v4

Information contained in this data sheet is up-to-date and correct as at the date of issue. As Adder Technology cannot control or anticipate the conditions under which this product may be used, each user should review the information in the specific context of planned use. Images are for illustrative purposes only.

ADDER TECHNOLOGY

Saxon Way, Bar Hill,
Cambridge, UK, CB23 8SL.
Tel: +44 (0)333 2079766 Fax: +44 (0)1954 780081
email: sales@adder.com www.adder.com

ADDER CORPORATION

324 Graf Road, Newburyport,
MA, 01950, United States.
Tel: +1 888 932 3337 Fax: +1 888 275 1117
email: usasales@adder.com www.adder.com

ADDER TECHNOLOGY ASIA PACIFIC

73 Ubi Road 1, # 08-62, Oxley Bizhub, 408733,
Singapore.
Tel: +65 6288 5767 Fax: +65 6284 1150
email: asiasales@adder.com www.adder.com

ADDER®

Adder Technology Limited, West Walk Building,
110 Regent Road, Leicester, LE1 7LT
(Registered in England and Wales No. 01823478)