

# ADDERLink™ XD150FX

Digital KVM Extender

DVI video extender with USB2.0 over a single duplex fiber cable.



## Features

### Perfect digital video, real-time control

The video extension system is visually lossless with no visible artefacts or latency allowing you to be certain of quality and control whilst separated from the computer.

### Single duplex LC fiber cable required

Video, USB2.0 and audio all pass along a single duplex LC fiber cable.

### Flexible extension distances from 150m/492ft to 4km/2.4mi

The unit is fitted with SFP cages allowing different types of fiber to be utilized. Distance is dependent on the cable type and fiber module. See table on next page for details.

### USB2.0

Enables connection of any USB human interface device from mouse and keyboard through to touch screens, graphics tablets, jog shuttles, joysticks and 3D explorers. Mass storage devices and isochronous devices such as webcams and headsets can also be used.

### EDID management

The extender has an intelligent EDID management to allow the true characteristics of the monitor to be passed back to the computer.

### REST API

A REST (REpresentational State Transfer) API is available with all functionality to which authorized third party control systems can interface.

### Web interface control

The ADDERLink™ XD150FX (XD150FX) can be controlled and monitored via a web interface. Temperature and status are viewable and each function can be individually controlled. Web interface security is by HTTP digest authentication (RFC 2617) with username and password as requested information.

### Plug and Play

The XD150FX extender is delivered in a zero config state so you can plug in the units and start working with them straight away. There is no need for drivers or software to be installed.

### Bi-directional CD-quality analog audio

The unit delivers CD-quality stereo audio (24-bit sampling at 96kHz) is available to transfer audio between local and remote. A microphone and headphones are also supported.


### RS232 with flow control

RS232 can be passed between the units to a maximum 115K2 baud rate via the options port.

## Product In Brief

ADDERLink™ XD150FX is a high performance KVM extender that enables you to locate the critical computing hardware in a secure and temperature controlled environment away from the user workstation whilst maintaining the original user desktop experience.

- Resolutions up to 2560x1600 @60Hz
- 150m/492ft extension distance for OM2 multi-mode fiber
- 4km/2.4mi extension distance for a single-mode fiber. 400m/1312ft extension for OM4 fiber
- Hi-speed USB2.0 for mass storage devices: Keyboard, mouse, tablet and touchscreen
- Bi-directional analog audio (Line in/out with microphone & headphone support)
- RS232 with RTS/CTS flow control



## Technical Specifications

### Hardware compatibility

- All computers with DVI, USB and audio

### DVI interface

- The system supports resolutions to a maximum of 2560x1600 @60Hz

### USB 2.0

- Supports USB2.0 devices (Low, Full and Hi-speed)
- Isochronous devices are supported

### Software compatibility

- All known operating systems

### Connections

#### Transmitter (TX)

- DVI, 2x audio 3.5mm, USB Type-B, options port (6p6c), ethernet port (8p8c) and peripheral connections

#### Receiver (RX)

- DVI, audio 3.5mm (line in and out), audio 3.5mm (mic in and headphones), 4x USB Type-A and options port (6p6c)

### Physical design

#### Robust metal construction

- Dimensions: 169mm/6.65" (W) x 31mm/1.22" (H) x 120mm/4.8" (D)
- Weight: 0.6kg/1.3lbs

### Power

- 3 Pin Locking DC jack (2x power adapter included)

- 100-240VAC 50/60Hz
- 0.7A, input to power adapter
- 12VDC18W output from power adapter

### Environmental

- Operating temp: 0°C to 40°C/32°F to 104°F
- Humidity: 0-90% RH, non-condensing
- Altitude: 0-2000m/6562ft

### Approvals

- CE, FCC, UKCA

### Mean Time Between Failure (MTBF)

- 400,000 hours; calculated to Telecordia standard SR-332 issue 4 March 2016 @55°C/131°F

Fiber type	Fiber size	Fiber type	Coding Normal	Coding Military	Coding Print #	Dist.	SFP part	Conn. type
OM1	(62.5/125)	Multimode (TIA-492AAAA)	Orange	Slate	62.5/125	70m/229ft	SFP-MM-LC-10G	LC
OM2	(50/125)	Multimode (TIA-492AAB)	Orange	Orange	50/125	150m/492ft	SFP-MM-LC-10G	LC
OM3	(50/125)	Multimode (850nm Laser-optimized) (TIA-492AAAC)	Aqua	Undefined	850 LO 50/125	380m/1246ft	SFP-MM-LC-10G	LC
OM4	(50/125)	Multimode (850nm Laser-optimized) (TIA-492AAAC)	Aqua	Undefined	850 LO 50/125	400m/1312ft	SFP-MM-LC-10G	LC
OS1 and OS2	(9/125)	Single-mode (TIA-492C000/ TIA-492E000)	Yellow	Yellow	SM/ZDS, SM	4km/13123ft	SFP-SM-LC-10G	LC



XD150FX RX - Front & Rear



XD150FX TX - Front & Rear

## Ordering Information

**XD150FX-MM-XX:** Multi-mode Pair\*

**XD150FX-SM-XX:** Single-mode Pair\*

\* including TX and RX units

## What's in the Box?

**1x** XD150FX pair with PSUs

**2x** SFP modules

**2x** 3m/6.5ft Audio cable

**1x** 1.8m/5.9ft DVI-D dual link cable

**1x** quick start guide

## Accessories (Sold Separately)

**RMK8:** 19" rack mount kit - 2 units/1U slot

**RMK10:** Wall/desk mount kit

**RMK5V:** VESA rack mount kit for monitor mounting

**SFP-SM-LC-10G:** Single-mode 10G SFP with LC conns

**SFP-MM-LC-10G:** Multi-mode 10G SFP with LC conns

## About Adder

Adder is a leading developer and thought leader in connectivity solutions. Adder's advanced range of KVM switches, extenders and IP solutions enable the control of local, remote and global IT systems across the enterprise. The company distributes its products in more than 60 countries through a network of distributors, resellers and OEMs.

Adder has offices in China, Germany, Japan, the Netherlands, Singapore, Spain, France, Sweden, United Kingdom and United States.

To find out more, visit: [adder.com](http://adder.com)

### Global Headquarters

Tel: +44 (0)1954 780044 | Fax: +44 (0)1954 780081  
Email: [sales@adder.com](mailto:sales@adder.com)

### Americas

Tel: +1 888 932 3337 | Fax: +1 888 275 1117  
Email: [usasales@adder.com](mailto:usasales@adder.com)

### Asia Pacific

Tel: +65 6288 5767 | Fax: +65 6284 1150  
Email: [asiasales@adder.com](mailto:asiasales@adder.com)

All brand names and trademarks are the property of their respective owner. Copyright 2020 | Adder Technology Ltd. | ADDER\_DS029\_EN\_v15\_FINAL\_DD.indd  
Information contained in this data sheet is up-to-date and correct as at the date of issue. As Adder Technology cannot control or anticipate the conditions under which this product may be used, each user should review the information in the specific context of planned use. Images are for illustrative purposes only.

**ADDER**<sup>®</sup>  
THE IP KVM PEOPLE

DATA SHEET